

Voltage	DC24V		DC48V	
Servo motor code	ST04000230-24V	ST04000330-24V	ST04000230-48V	ST04000330-48V
Explosion-proof code	EX04000230-24V	EX04000330-24V	EX04000230-48V	EX04000330-48V
Mining type code	MA04000230-24V	MA04000330-24V	MA04000230-48V	MA04000330-48V
Radiation hardened code	F04000230-24V	F04000330-24V	F04000230-48V	F04000330-48V
Rated power (KW)	0.05	0.1	0.05	0.1
Rated current (A)	24.5	49	12.2	24.5
Rated speed (rpm)	3000	3000	3000	3000
Maximum speed (rpm)	3600	3600	3600	3600
Rated torque (N.m)	0.16	0.32	0.16	0.32
Peak torque (N.m)	0.48	0.96	0.48	0.96
Rotor inertia (kg.cm ²)	30	46	30	46
Class of protection	IP65	IP65	IP65	IP65
Voltage	DC72V		DC96V	
Servo motor code	ST04000230-72V	ST04000330-72V	ST04000230-96V	ST04000330-96V
Explosion-proof code	EX04000230-72V	EX04000330-72V	EX04000230-96V	EX04000330-96V
Mine type code	MA04000230-72V	MA04000330-72V	MA04000230-96V	MA04000330-96V
Radiation proof code	F04000230-72V	F04000330-72V	F04000230-96V	F04000330-96V
Rated power (KW)	0.05	0.1	0.05	0.1
Rated current (A)	8.2	16.3	6.1	12.2
Rated speed (rpm)	3000	3000	3000	3000
Maximum speed (rpm)	3600	3600	3600	3600
Rated torque (N.m)	0.16	0.32	0.16	0.32
Peak torque (N.m)	0.48	0.96	0.48	0.96
Rotor inertia (kg.cm ²)	30	46	30	46
Class of protection	IP65	IP65	IP65	IP65
Voltage	AC220V			
Servo motor code	ST04000230-220V		ST04000330-220V	
Explosion-proof code	EX04000230-220V		EX04000330-220V	
Mine type code	MA04000230-220V		MA04000330-220V	
Radiation proof code	F04000230-220V		F04000330-220V	
Rated power (KW)	0.05		0.1	
Rated current (A)	0.65		1.27	
Rated speed (rpm)	3000		3000	
Maximum speed (rpm)	3600		3600	
Rated torque (N.m)	0.16		0.32	
Peak torque (N.m)	0.48		0.96	
Rotor inertia (kg.cm ²)	30		46	
Class of protection	109		119	
Servo motor code	0.2		0.4	
Explosion-proof code	IP65		IP65	